



# Cisco

## 500-901 Exam

### Cisco Data Center Unified Computing Infrastructure Design Exam

**Thank you for Downloading 500-901 exam PDF Demo**

**You can Buy Latest 500-901 Full Version Download**

<https://www.certkillers.net/Exam/500-901>

<https://www.certkillers.net>

## Version: 8.0

---

### Question: 1

---

What is the purpose of a virtual switch?

- A. Virtual switches manage storage requests from virtual machines
- B. Virtual switches present NICs to virtual machines for network connectivity
- C. Virtual switches recommend QoS options to the hypervisor for network connectivity
- D. Virtual switches present NICs to the UCSM for network connectivity

---

**Answer: B**

---

---

### Question: 2

---

You dissociated a Database Server Service Profile from your existing UCS C240 M4. Then, you associate a Web Server Service Profile to this UCS C240 M4. The Database Server Service Profile enabled a Scrub Policy enabled for Disk Scrub. The Web Server Service Profile contains a Scrub Policy disabled for Disk Scrub. What will happen after the reboot?

- A. The process will fail because the Service Profiles are fundamentally efferent
- B. The process will succeed, and server disk content will be preserved
- C. The process will fail because of the differences in the Scrub Policies
- D. The process will succeed, but server disk content will be lost

---

**Answer: C**

---

---

### Question: 3

---

You are creating Boot Policy to have your Cisco UCS Server boot from SAN. What option shows the correct process?

- A. Include a vHBA in the Boot Order list, provide a Boot LUN ID, and provide the WWPN address for the Boot Target.
- B. Include a vHBA in the Boot Order list, provide a SAN ID, and provide the WWPN address for the Boot Target.
- C. Include two VHBAs in the Boot Order list (vHBA-A and vHBA-B for redundancy), provide a Boot Lun ID for each vHBA, and provide the WWPN address for the Boot Target.
- D. Include two vHBAs in the Boot Order list (vHBA-A and vHBA-B for redundancy), provide a SAN ID, and provide the WWPN address for the Boot Target.

---

**Answer: A**

---

---

### Question: 4

---

An administrator has configured an NPV traffic map for a new server interface, none of the uplinks in the traffic map are operational. What is the resulting action?

- A. The traffic map will be disregarded and an uplink in the interface VSAN will be selected
- B. The default VSAN uplink will be used if operational.
- C. The server will remain in a nonoperational state.
- D. The server interface will signal an FDISC message to the fabric switch.

---

**Answer: C**

---

CertKillers.net

## Thank You for trying 500-901 PDF Demo

To Buy Latest 500-901 Full Version Download visit link below

<https://www.certkillers.net/Exam/500-901>

## Start Your 500-901 Preparation

[Limited Time Offer] Use Coupon “CKNET” for Further discount on your purchase. Test your 500-901 preparation with actual exam questions.

<https://www.certkillers.net>